

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION

### **NOTICE OF ACCEPTANCE (NOA)**

MIAMI-DADE COUNTY, FLORIDA PRODUCT CONTROL SECTION 11805 SW 26 Street, Room 208 T (786) 315-2590 F (786) 315-2599 www.miamidade.gov/economy

PGT Industries, Inc. 1070 Technology Drive North Venice, FL 34275

Scope:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER-Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami-Dade County) and/ or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code. This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series "SH -500 Vinyl" White PVC Single Hung Window - L.M.I.

APPROVAL DOCUMENT: Drawing No. 5191–1, Series titled "Vinyl Single Hung Window, Large Missile Impact", sheets 1 through 11 of 11, dated 08/07/08 with revision "C" dated 10/07/11, prepared by manufacturer, signed and sealed by Anthony Lynn Miller, P. E., bearing the Miami–Dade County Product Control Section Renewal stamp with the Notice of Acceptance number and Expiration date by the Miami–Dade County Product Control Section.

### MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, model/ series, and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**REVISION** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/ or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA renews NOA No. 11-1013.19 and consists of this page 1 and evidence pages E-1 and E-2, as well as approval document mentioned above.

The submitted documentation was reviewed by Jaime D. Gascon, P. E.





NOA No. 13-1009.05 Expiration Date: January 08, 2019 Approval Date: November 14, 2013

Page 1

### PGT Industries, Inc.

### NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

### A. DRAWINGS

1. Manufacturer's die drawings and sections.

(Submitted under previous NOA No. 08-0820.14)

Drawing No. 5191–1, series titled "Vinyl Single Hung Window, Large Missile Impact", sheets 01 through 11 of 11, dated 08/07/08 with revision "C" dated 10/07/11, prepared by manufacturer, signed and sealed by Anthony Lynn Miller, P. E. (Submitted under previous NOA No. 11–1013.19)

### B. TESTS

1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94

- 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
- 3) Water Resistance Test, per FBC, TAS 202-94
- 4) Large Missile Impact Test per FBC, TAS 201-94
- 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
- 6) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

along with marked-up drawings and installation diagram of a vinyl fixed window, prepared by Fenestration Testing Laboratory, Inc., Test Report No. FTL-5710, dated 08/13/08, signed and sealed by Carlos S. Rionda, P. E.

(Submitted under previous NOA No. 08-0820.14)

- 2. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
  - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
  - 3) Water Resistance Test, per FBC, TAS 202-94
  - 4) Large Missile Impact Test per FBC, TAS 201-94
  - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
  - 6) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

along with marked-up drawings and installation diagram, prepared by Architectural Testing, Inc., Test Report No. ATI-84576.01-401-47, dated 10/31/08, signed and sealed by Joseph A. Reed, P. E.

(Submitted under previous NOA No. 08-0820.14 - For Reference only)

### C. CALCULATIONS

1. Anchor verification calculations and structural analysis, complying with FBC-2010, prepared by manufacture, dated 10/07/11, signed and sealed by Anthony Lynn Miller, P. E.

(Submitted under previous NOA No. 11-1013.19)

2. Glazing complies with ASTM E1300-04

### D. QUALITY ASSURANCE

1. Miami-Dade Department of Regulatory and Economic Resources (RER).

Jaime D. Gascon, P. E.

Product Control Section Supervisor

NOA No. 13-1009.05

Expiration Date: January 08, 2019 Approval Date: November 14, 2013

### PGT Industries, Inc.

### NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

#### E. MATERIAL CERTIFICATIONS

- 1. Notice of Acceptance No. 13-0129.27 issued to E.I. DuPont DeNemours & Co., Inc. for their "DuPont Butacite® PVB Interlayer" dated 04/11/13, expiring on 12/11/16.
- 2. Notice of Acceptance No. 11–0830.09 issued to Mikron Industries, Inc., for their "White Rigid PVC Exterior Extrusions for Windows and Doors" dated 10/6/11, expiring on 12/26/16.

### F. STATEMENTS

- 1. Statement letter of conformance and complying with FBC-2010, issued by manufacture, dated 10/07/11, signed and sealed by Anthony Lynn Miller, P. E. (Submitted under previous NOA No. 11-1013.19)
- 2. Statement letter of no financial interest, issued by manufacture, dated 10/07/11, signed and sealed by Anthony Lynn Miller, P. E. (Submitted under previous NOA No. 11–1013.19)
- 3. Laboratory compliance letter for Test Report No. FTL-5710, issued by Fenestration Testing Laboratory, Inc., dated 08/13/08, signed and sealed by Carlos S. Rionda, P. E. (Submitted under NOA No. 08-0820.14)
- 4. Laboratory compliance letter for Test Report No. ATI-84576.01-401-47, issued by Architectural Testing, Inc., dated 10/31/08, signed and sealed by Joseph A. Reed, P. E. (Submitted under NOA No. 08-0820.14 For Reference only)

#### G. OTHERS

1. Notice of Acceptance No. 11–1013.19, issued to PGT Industries, Inc. for their Series "SH–500–Vinyl White PVC Single Hung Window – L.M.I.", approved on 12/08/11 and expiring on 01/08/14.

Jaime D. Gascon, P. E. Product Control Section Supervisor

NOA No. 13-1009.05

Expiration Date: January 08, 2019 Approval Date: November 14, 2013

### GENERAL NOTES: LARGE MISSILE IMPACT SINGLE HUNG BOX FRAME AND INTEGRAL FIN WINDOWS

- 1. GLAZING OPTIONS:
- A. 3/4" LAMI I.G. GLASS COMPRISED OF (1) LITE OF 1/8" TEMPERED OR ANNEALED GLASS, AIRSPACE AND 5/16" LAMINATED GLASS WHICH IS COMPRISED OF (2) LITES OF 1/8" ANNEALED GLASS WITH AN .090 INTERLAYER OF DUPONT PVB.
- B. 7/8" LAMI I.G. GLASS COMPRISED OF (1) LITE OF 1/8" TEMPERED OR ANNEALED GLASS, AIRSPACE AND 5/16" LAMINATED GLASS WHICH IS COMPRISED OF (2) LITES OF 1/8" ANNEALED GLASS WITH AN .090 INTERLAYER OF DUPONT PVB.
- 2. CONFIGURATIONS: 1/1 AND PROVIEW
- 3. DESIGN PRESSURES: -70/+60 PSF (ALL GLASS TYPES LISTED ABOVE)
  - A. NEGATIVE DESIGN LOADS BASED ON TESTED PRESSURE AND GLASS TABLES ASTM E 1300-02.
  - B. POSITIVE DESIGN LOADS BASED ON WATER TEST PRESSURE AND GLASS TABLES ASTM E 1300-02.
  - C. IF A TEMPERED CAP IS USED MAX. DP IS -50/+50 PSF.
- 4. ANCHORAGE: THE 33 1/3% STRESS INCREASE <u>HAS NOT</u> BEEN USED IN THE DESIGN OF THIS PRODUCT. MATERIALS, INCLUDING BUT NOT LIMITED TO STEEL SCREWS, THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF THE FLORIDA BUILDING CODE, CURRENT EDITION. SEE SHEETS 9 THROUGH 11 FOR ANCHORAGE DETAILS.
- 5. SHUTTERS ARE NOT REQUIRED FOR UNITS LESS THAN 30'.
- 6. REFERENCES: TEST REPORTS FTL-5710.

  ANSI/AF&PA NDS-2001 FOR WOOD CONSTRUCTION

  ADM-2000 ALUMINUM DESIGN MANUAL
- 7. THIS PRODUCT HAS BEEN DESIGNED & TESTED TO COMPLY WITH THE REQUIREMENTS OF THE FLORIDA BUILDING CODE, INCLUDING THE HIGH VELOCITY HURRICANE ZONE (HVHZ).

NOA DRAWING TABLE OF CONTENTS
SHEET
GENERAL NOTES1
ELEVATIONS 2
GLAZING DETAILS 3
GLAZING DETAILS 4
SECTIONS, I.F. FRAME5
SECTIONS, BOX FRAME 6
PARTS LIST 7
EXTRUSIONS8
ANCHORAGE SPACING, BOX FRAME 9
ANCHORAGE DETAILS, BOX FRAME10
ANCHORAGE DETAILS, I.F. FRAME 11

PRODUCT RENEWED
as complying with the Florida
Building Code
Acceptance No
Expiration Date

By
Miami Dade Product Control

PRODUCT REVISED as complying with the Florida Building Code

Building Code
Acceptance No 11-1013
Expiration Date JAN 8

By Mami Dade Product Control

NO. 58705

\* NO. 58705


A. LYNN MILLER, P.E.


FL P.E.# 58705


	Reyed By:	Date:	Revisions:				
ı	D.G.	11/25/08	A	PER MIAMI-DADE LETTER DATED 10/31/08	]		
ĺ	Revad By:	Date:	Revisions:		1070 TECHNOLOGY DRIVI		
	D.G.	12/18/08	В	NO CHANGE THIS SHEET	NOKOMIS, FL 34275		
ĺ	Reysd By:	Dale:	Revisions:		1		
	JJ	10/07/11	C	2010 FBC UPDATE	P.O. BOX 1529		
	Drawn By:	Date:	Checked By:	Dale:	NOKOMIS, FL 34274		
	D.G.	8/07/08					





GENERAL NOTES										
•	Vinyl Single	™ Vinyl Single Hung Window, Large Missile Impact								
•	Series/Model:	Scale:		Drewing No.	Rev:					
	SH500	NTS	1	a 1	1	5191-1	C			












ITEM	DWG NO.	PART#	DESCRIPTION
1	9521	65163	INTEGRAL FIN FRAME HEAD & JAMB
2	9871	69871	BOX FRAME HEAD & JAMB
3	9520	65164	INTEGRAL FIN FRAME SILL
4	9870	69870	BOX FRAME SILL
5	7940	65102	FIXED MEETING RAIL
6	7126.1	65103	MEETING RAIL REINFORCEMENT
7	7942	65109	SASH STOP
8	8873	65117	BALANCE COVERS
9	7092	65105	SASH INTERLOCK
10		61644W	WSTP., .187 X .270 FIN SEAL
11	7092.1	65114	SASH REINFORCEMENT
12	7093	65106	SASH SIDE RAIL
13	7745	65113	SASH LIFT RAIL
14	1669	71669SP	MR SUPPORT PLATE
15	15B110	71694	TILT BALANCE SHOES
16	1686	7FPHPSSPF	PIVOT BARS
17		76208SLAW	CAM SWEEP LOCK
18		76133SLKW	CAM SWEEP LOCK KEEPER
19		79803WF	WEEP HOLE COVER
20		7675RHTL	RHTILT LATCH
21		7675LHTL	LH TILT LATCH
22		71669SP	ALUM, SCREW SUPPORT PLATE
23		71038W	INSTALL HOLE PLUG
24		71684K	SETTING BLOCK
25		71684AK	SETTING BLOCK - SELF ADHESME
26		76X1FPTWX	6 X 1" FH TECH (410 SS PAINTED)
27		7612FPTWX	6 X 1/2" FH (410 SS PAINTED)
28		76X2TPA410X	6 X 2" TH VINYL SCREW SS
29		78X114FPAB410X	
30		8X1FPAX	#8 X 1"

TEM	DWG NO.	PART #	DESCRIPTION
			7/8" LAMI I.G. GLASS: 1/8" TEMPERED OUTBOARD -
31			AIRSPACE - 1/8" ANNEALED090 PVB INTERLAYER -
			1/8" ANNEALED (5/16" LAMI)
-	ļ		7/8" LAMI I.G. GLASS: 1/8" ANNEALED OUTBOARD -
32	] ]		AIRSPACE - 1/8" ANNEALED090 PVB INTERLAYER -
			1/8" ANNEALED (5/16" LAM)
33			
34			
			3/4" LAMILG, GLASS: 1/8" TEMPERED OUTBOARD -
35	1		AIRSPACE - 1/8" ANNEALED090 PVB INTERLAYER -
00			1/8" ANNEALED (5/16" LAMI)
			3/4" LAMILG. GLASS: 1/8" ANNEALED OUTBOARD -
36			AIRSPACE - 1/8" ANNEALED090 PVB INTERLAYER -
			1/8" ANNEALED (5/16" LAMI)
37	1		
38	† †		
39			SILICONE DOW 1199
	6492	65112	GLAZING BEAD
40	1 0492	00112	



**DWG NO. 8483** 

PRODUCT RENEWED as complying with the Florida Building Code Acceptance No. 12-1009.


Reparation Date 12-1009.


Miami Dade Product Control


PRODUCT REVISED
as complying with the Florida,
Building Code


Acceptance No 1/-

Expiration Date JAN. 8









## SASH REINFORCEMENT

MAT'L: Alum. (6063-T6) DWG NO. 7092.1

### ITEM 5, FIXED MEETING RAIL

MAT'L: White Ridged PVC by MIKRON Industries, Inc. **DWG NO. 7940** 

Α

tevision B

Revisions C

Reved By: Date: D.G. 11/25/08

r: Date: 12/18/08

D.G. 08/07/08

Date: 10/07/11

Reved By: D.G.

Reved By:

### ITEM 6, FIXED MTG. RAIL REINF.

MAT'L: Alum. (6063-T6) DWG NO. 7126.1

### ITEM 9, SASH INTERLOCK

MAT'L: White Ridged PVC by MIKRON Industries, Inc. DWG NO. 7092

SH500


PER MIAMI-DADE LETTER DATED 10/31/08		
ADDED DIMENSIONS TO ALUM. EXTRUSIONS	1070 TECHNOLOGY DRIVE NOKOMIS, FL 34275	
NO CHANGE THIS SHEET	P.O. BOX 1529	
Dolor	NOKOMIS, FL 34274	Visibly Bett



Description:
PARTS LIST AND EXTRUSIONS


Vinyl Single Hung Window, Large Missile Impact NTS C 7 × 11 5191-1

Miami Dade Product Control TY LYNN MILES LICENO MIL A. LYNN MILLER, P.E. FL P.E.# 58705




#### ANCHOR QUANTITIES TABLE 1 WINDOW WIDTH View 48 52 1/8 1/1 16 20 24 28 32 36 40 Sash Fixed 2 36 24 1 1 1 1 3 W 25 45 30 1 1 1 1 1 1 1 1 1 1 3 2 2 2 3 30 54 36 Ν 1 | 1 | 1 | 2 | 1 | 2 D 2 3 3 35 62 1/2 42 0 2 1 2 2 1 2 1 1 2 1 | 2 1 | 2 | 1 | 2 2 | 2 | 2 3 W 40 48 2 2 2 2 2 2 2 2 2 2 2 2 2 2 3 2 45 54 Η 2 2 2 2 2 2 2 2 Ε 2 50 60 2 | 3 G 2 2 3 55 66 2 3 4 3 2 | 3 2 3 2 3 3 2 60 72 2 3 2 3 2 3 3 2 3 3 3 3 4 3 4 2 3 2 75 62 1/2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 4 3 4

Example: 52.125 x 75 For 1/1 Windows



Example: 52.125 x 62.500 For View Windows



NOTE: FOR VIEW WINDOWS USE VIEW FIXED WINDOW HEIGHT FOR A NCHOR QUANTITY IN HEAD AND ABOVE THE MTR, AND USE THE VIEW SASH WINDOW HEIGHT FOR ANCHOR QUANTITY BELOW THE MTR. MAXIMUM HEIGHT FOR VIEW WINDOW IS 62 1/2".

### NOTE: FOR VIEW WINDOW THE LARGEST CAN NOT EXCEED THE TESTED SIZE.

Reved By:	Dale:	Revisions:		
D.G.	11/25/08	A	PER MIAMI-DADE LETTER DATED 10/31/08	
Reved By:	Date:	Revisions:		11070 TECHNOLOGY DRIVE
D.G.	12/18/08	В	ADDED AND MODIFIED VIEW WINDOW EXAMPLES	NOKOMIS, FL 34275
Reved By:	Date:	Revisions:		1
JJ	10/07/11	C	NO CHANGE THIS SHEET	P.O. BOX 1529
Drawn By:	Date:	Checked By:	Dalo:	NOKOMIS, FL 34274
l na	1 08/07/08	1		1





### ANCHORAGE NOTES FOR BOX FRAME:

- 1. ANCHOR TYPES: 1 3/16" ULTRACONS
- 2 #10 SCREWS

SILL - ANCHORS NOT REQUIRED

- 2. ANCHOR LOCATIONS ARE BASED ON THE FOLLOWING DIMENSIONS. HEAD - 6" MAX, FROM TOP CORNERS JAMBS - 9" MAX. FROM TOP CORNERS\* (\*NOT TO EXCEDE 1/4 OF TOTAL WINDOW HEIGHT) 6" MAX. FROM BOTTOM CORNERS 4" MIN. BELOW MTG, RAIL
- 3. INSTALL PER THE ADJACENT TABLE ANCHOR QUANTITIES USING THE DIMENSIONAL CRITERIA OF NOTE 2.
- 4. ANCHORAGE SHOWN FOR BOX FRAME WITH OR WITHOUT OPTIONAL FLANGE.
- 5. FOR INTEGRAL NAIL FIN FRAME ANCHORAGE, SEE SHEET 11.





PRODUCT RENEWED as complying with the Florida Building Code 13-1009.05
Acceptunce No Explinition Date 2108/2019 Miami Dade Product Control

¬RODUCT REVISED as complying with the Florida Building Code Acceptance No 11-1013.19 Expiration Date 150. 8 2014 By Maruel Jers

Miami Dade Product Control

No. 58705

No. 58705

TO LO LO LIVE
STATE OF . FLORIDA. SONAL EN A. LYNN'MILLER, P.E.


ANCHORAGE SPACING Vinyl Single Hung Window, Large Missile Impact

9 4 11

NTS


SH500

C5191-1



## JAMB W/ BOX FRAME THROUGH FRAME INTO 2x WOOD

# HEAD W/ BOX FRAME THROUGH FRAME INTO 2x WOOD



# JAMB W/ BOX FRAME THROUGH FRAME INTO CONCRETE 1x BUCK OPTIONAL

# HEAD W/ BOX FRAME THROUGH FRAME INTO CONCRETE 1x BUCK OPTIONAL

### NOTES:

- 1. FOR CONCRETE APPLICATIONS IN MIAMI-DADE COUNTY, USE ONLY MIAMI-DADE COUNTY APPROVED 3/16" ULTRACON, EMBEDED 1 3/8" MIN., DISTANCE FROM ANCHOR TO CONCRETE EDGE IS 1" MINIMUM.
- 2. FOR WOOD APPLICATIONS IN MIAMI-DADE COUNTY, USE #10 STEEL SCREW, EMBEDED 1 3/8" MIN..
- 3. WOOD BUCKS DEPICTED IN THE SECTIONS ON THIS PAGE AS 1x ARE BUCKS WHOSE TOTAL THICKNESS IS LESS THAN 1 1/2". 1x WOOD BUCKS ARE OPTIONAL IF UNIT CAN BE INSTALLED DIRECTLY TO SOLID CONCRETE. WOOD BUCKS DEPICTED AS 2x ARE 1 1/2" THICK OR GREATER. INSTALLATION TO THE SUBSTRATE OF WOOD BUCKS TO BE ENGINEERED BY OTHERS OR AS APPROVED BY AUTHORITY HAVING JURISDICTION.
- 4. FOR ATTACHMENT TO ALUMINUM: THE MATERIAL SHALL BE A MINIMUM STRENGTH OF 6063-T5 AND A MINIMUM OF 1/8" THICK. THE ALUMINUM STRUCTURAL MEMBER SHALL BE OF A SIZE TO PROVIDE FULL SUPPORT TO THE WINDOW FRAME SIMILAR TO THAT SHOWN IN THESE DETAILS FOR 2x WOOD BUCKS. THE ANCHOR SHALL BE A #10 SHEET METAL SCREW WITH FULL ENGAGEMENT INTO THE ALUMINUM. IF THESE CRITERIA ARE MET, THE RESPECTIVE DESIGN PRESSURES AND ANCHORAGE SPACING FOR ULTRACONS MAY BE USED.

`	GI AGING LONG GENTAGONG WIAT BE COLD.										_
Reved By: D.G.	Date: 11/25/08	Revisions:	PER MIAMI-DADE LETTER DATED 10/31/08			ANCHORAGE DETAILS - BOX FRAM					7
Reved By: D.G.	Date: 12/18/08	Revisions: B	NO CHANGE THIS SHEET	1070 TECHNOLOGY DRIVE NOKOMIS, FL 34275		Title:					
Reved By: JJ	Date; 10/07/11	Revisions:	NO CHANGE THIS SHEET	P.O. BOX 1529			e Hung Tscale:	g Window, L	arge Missile Imp	Revi	
Drawn By: D.G.	Date; 08/07/08	Checked By	Date; .G.	NOKOMIS, FL 34274	Visibly Better	SH500	NTS		5191-1	C	

PRODUCT RENEWED
as complying with the Florida
Building Code
Acceptance No
Expiration Date

By
Miami Dade Product Control

PRODUCT REVISED
as complying with the Florida

Building Code
Acceptance No //- 10
Expiration Date //AL

By Miami/Dade Product Control


No. 58705

No. 58705

No. 58705

A. LYNN MILLER, P.E.

FL P.E.# 58705



JAMB W/ NAIL FIN THRU NAIL FIN INTO WOOD FRAMING

**HEAD W/ NAIL FIN** THRU NAIL FIN INTO WOOD FRAMING THRU NAIL FIN INTO WOOD FRAMING

SILL W/ NAIL FIN

### NOTES:

- 1. FOR INTEGRAL FIN APPLICATIONS IN MIAMI-DADE COUNTY, USE 1/8" DIA. x 1 1/2" NAIL.
- 2. WOOD BUCKS DEPICTED IN THE SECTIONS ON THIS PAGE AS 1x ARE BUCKS WHOSE TOTAL THICKNESS IS LESS THAN 1 1/2". 1x WOOD BUCKS ARE OPTIONAL IF UNIT CAN BE INSTALLED DIRECTLY TO SOLID CONCRETE. WOOD BUCKS DEPICTED AS 2x ARE 1 1/2" THICK OR GREATER. INSTALLATION TO THE SUBSTRATE OF WOOD BUCKS TO BE ENGINEERED BY OTHERS OR AS APPROVED BY AUTHORITY HAVING JURISDICTION.
- 3. FOR ATTACHMENT TO ALUMINUM: THE MATERIAL SHALL BE A MINIMUM STRENGTH OF 6063-T5 AND A MINIMUM OF 1/8" THICK. THE ALUMINUM STRUCTURAL MEMBER SHALL BE OF A SIZE TO PROVIDE FULL SUPPORT TO THE WINDOW FRAME SIMILAR TO THAT SHOWN IN THESE DETAILS FOR 2x WOOD BUCKS. THE ANCHOR SHALL BE A #10 SHEET METAL SCREW WITH FULL ENGAGEMENT INTO THE ALUMINUM. IF THESE CRITERIA ARE MET, THE RESPECTIVE DESIGN PRESSURES AND ANCHORAGE SPACING FOR ULTRACONS MAY BE USED.

i varan ol.	Date.	rterisions:			
D.G.	11/25/08	A	PER MIAMI-DADE LETTER DATED 10/31/08		-
Reysd By:	Date:	Revisions:	, , , , , , , , , , , , , , , , , , , ,	1070 TECHNOLOGY DRIVE	ı
D.G.	12/18/08	В	NO CHANGE THIS SHEET	NOKOMIS, FL 34275	1
Reysd By:	Dale:	Revisions:	·		
JJ	10/07/11	C	NO CHANGE THIS SHEET	P.O. BOX 1529	į <del>–</del>
Drawn By:	Date:	Checked By:	Date:	NOKOMIS, FL 34274	ı
ם או	DRIDZIDR -	1	**		ı



SH500

ANCHORAGE DETAILS - Integral Fin Frame Vinyl Single Hung Window, Large Missile Impact NTS 11 a 11 5191-1 C

Building Code Miami Dade Product Control RODUCT REVISED 3 complying with the Florida Building Code Acceptance No Expiration Date JAN. & Miami/Dade Product Control A. LYNN MILLER, P.E. SONAL EN

FL P.E.# 58705

PRODUCT RENEWED as complying with the Florida